



## **PB-01**

## **Signposted Waist Stretching Device**

- The standing and sitting waist operating device with panel consists of two stations that can be used by one person or two people.
- It is designed for use to exercise and stretch the waist and leg muscles.
- Carrier pipes are manufactured from pipes with a diameter of at least Ø 114 mm and a wall thickness of 2.5-3 mm.
- The Ø114 SDM pipe will be used at 4 points, where the apparatus to be used in connecting the main carriers and mounting the panel will be welded.
- Digital printing is made on 2 mm thick dkp sheet material on the panel, which will be mounted on a minimum 4 mm apparatus on the main carrier.
- The moving parts connected to the main body are manufactured with a wall thickness of at least Ø 60 mm and 2.5-3 mm and in one piece with a special twist.
- The main body flashes are manufactured by laser cutting from ST37 sheet with a thickness of 8 mm and a size of 280x280 mm and 4 pieces of flag sheet are welded in order to increase the flange strength.
- Anchor covers measuring Ø114 mm in accordance with the design to fully grasp the carrier pipes are used to close the open-ended pipes in fitness products.
- Anchor covers are produced from polyethylene plastic material by LLDPE (Linear Low Density Polyethylene) injection method.
- It is designed to be resistant to UV lights and not to harm the user.
- It is manufactured as a double wall and its installation is provided with a screwing system.
- The seat is made of self-colored polyethylene material.
- In the movable part of the seated waist movement part, there is an internal support system and a foot platform made of Ø 60 mm 2,5-3 mm thick pipe.
- In the standing waist operating station, the rotating platforms are manufactured from embossed sheet metal with a thickness of 2.5-3 mm Ø 300 mm in a style that will prevent the user's feet from slipping.
- The circular edge of the rotating platform is reinforced with metal material with a thickness of 2.5-3 mm and a width of 16 mm.
- Six 6205 2RS bearings are used in the product.
- Fitness roof is produced from polyethylene plastic material by rotation method.
- The upper part is designed serrated to prevent rain, snow, etc. from puddles of water.
- It is mounted to the main body with protrusions located at the base.

- There are no sharp edges and corners that will harm the user.



<b>Dimensions</b>	Width	103 cm
	Length	128 cm
	Height	251 cm